

SAFETY DATA SHEET Super Hybrid SH-PRO comp A

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Super Hybrid SH-PRO comp A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier G&B Fissaggi Srl

Corso Savona 22

10029, Villastellone (TO)

Italy

+39 011 96 19 433 +39 011 96 19 382/ 639

Web www.gebfissaggi.com

Contact person info@gebfissaggi.com

1.4. Emergency telephone number

Emergency telephone +39 011 96 19 433 (8.30 - 12.30 /13.30 - 17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Super Hybrid SH-PRO comp A

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P273 Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P264 Wash contaminated skin thoroughly after handling. P302+P352 IF ON SKIN: Wash with plenty of water.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

VINYL TOLUENE 10-20%

CAS number: 25013-15-4 EC number: 246-562-2 REACH registration number: 01-

2119622074-50

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

TITANIUM DIOXIDE >0.5 <1.0%

CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-

2119489379-17

Classification

Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

Super Hybrid SH-PRO comp A

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause respiratory irritation.

Ingestion May cause discomfort if swallowed.

Skin contact May cause skin irritation/eczema.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion

products

Oxides of carbon.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. For waste disposal,

see Section 13.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautionsDo not use in confined spaces without adequate ventilation and/or respirator.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away

from oxidising materials, heat and flames.

Storage class Chemical storage.

7.3. Specific end use(s)

Super Hybrid SH-PRO comp A

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

VINYL TOLUENE (CAS: 25013-15-4)

DNEL Industry - Inhalation; Long term systemic effects: 37 mg/m³

Industry - Inhalation; Long term local effects: 37 mg/m³

REACH dossier information

PNEC - Fresh water; 0.0498 mg/l

marine water; 0.002 mg/lIntermittent release; 0.013 mg/l

- STP; 1 mg/l

Sediment (Freshwater); 0.684 mg/kgSediment (Marinewater); 0.0684 mg/kg

- Soil; 0.133 mg/kg

REACH dossier information

TITANIUM DIOXIDE (CAS: 13463-67-7)

DNEL Industry - Inhalation; Long term systemic effects: 10 mg/m³

REACH dossier information

PNEC - Fresh water; 0.127 mg/l

- marine water; 1.0 mg/l

- Intermittent release; 0.61 mg/l

- STP; 100 mg/l

Sediment (Freshwater); 1000 mg/kgSediment (Marinewater); 100 mg/kg

- Soil; 100 mg/kg

REACH dossier information

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Super Hybrid SH-PRO comp A

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

> smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of

skin. When using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid Colour Beige. Odour Aromatic.

Odour threshold Not determined.

pН Not applicable.

Melting point Not determined.

Initial boiling point and range >165°C @

53°C Flash point

Evaporation rate Not determined. Not determined. **Evaporation factor** Not determined. Flammability (solid, gas) Upper/lower flammability or

explosive limits

Not determined.

Other flammability Not determined. Vapour pressure 6 hPa @ 20°C Vapour density Not determined.

Relative density 1.65 - 1.75 @ 20°C

Bulk density Not applicable. Insoluble in water Solubility(ies)

Partition coefficient Not determined. **Auto-ignition temperature** Not determined. **Decomposition Temperature** Not determined.

> 60 S ISO2431; Kinematic viscosity > 20.5 mm²/s. Viscosity

Explosive properties No information available.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Super Hybrid SH-PRO comp A

Reactivity The following materials may react with the product: Organic peroxides/hydroperoxides.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 79.09

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Irritating to skin. Irritating to eyes.

Route of exposure Skin and/or eye contact.

Medical symptoms Irritation of eyes and mucous membranes. Skin irritation.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

VINYL TOLUENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,255.0

mg/kg)

Species Rat

ATE oral (mg/kg) 2,255.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 4,500.0

mg/kg)

Super Hybrid SH-PRO comp A

Species Rat

ATE dermal (mg/kg) 4,500.0

Acute toxicity - inhalation

ATE inhalation (vapours 11.0

mg/l)

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

VINYL TOLUENE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 23.4 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.3 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: 2.6 mg/l, Selenastrum capricornutum

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

VINYL TOLUENE

Partition coefficient log Pow: 3.36

12.4. Mobility in soil

Mobility Not applicable.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

Super Hybrid SH-PRO comp A

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1866 UN No. (IMDG) 1866 UN No. (ICAO) 1866

14.2. UN proper shipping name

Proper shipping name

RESIN SOLUTION

1866

(ADR/RID)

UN No. (ADN)

Proper shipping name (IMDG) RESIN SOLUTION
Proper shipping name (ICAO) RESIN SOLUTION
Proper shipping name (ADN) RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 3
ADR/RID classification code F1
ADR/RID label 3
IMDG class 3
ICAO class/division 3
ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III
IMDG packing group III
ICAO packing group III
ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

Super Hybrid SH-PRO comp A

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 09/05/2018

Version number 3.000

Supersedes date 07/12/2017

SDS number 20997

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Revision date: 05/12/2017



SAFETY DATA SHEET Super Hybrid SH-PRO comp B

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Super Hybrid SH-PRO comp B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Catalyst.

1.3. Details of the supplier of the safety data sheet

Supplier G&B Fissaggi Srl

Corso Savona 22

10029, Villastellone (TO)

Italy

+39 011 96 19 433 +39 011 96 19 382/ 639

Web www.gebfissaggi.com

Contact person info@gebfissaggi.com

1.4. Emergency telephone number

Emergency telephone +39 011 96 19 433 (8.30 - 12.30 /13.30 - 17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health May cause skin disorders if contact is repeated or prolonged. The product is irritating to eyes

and skin.

Environmental The product contains a substance which is very toxic to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

Physicochemical Not considered to be a significant hazard due to the small quantities used.

2.2. Label elements

Pictogram





Signal word Warning

Revision date: 05/12/2017

Super Hybrid SH-PRO comp B

Hazard statements H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.

Contains BENZOYL PEROXIDE

Supplementary precautionary

P264 Wash contaminated skin thoroughly after handling.

statements

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P411 Store at temperatures not exceeding °C/77°F.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BENZOYL PEROXIDE 10-15%

CAS number: 94-36-0 EC number: 202-327-6 REACH registration number: 01-

2119511472-50

M factor (Acute) = 10 M factor (Chronic) = 10

Classification

Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR 5-10%

CAS number: 670241-72-2 EC number: 447-010-5 REACH registration number: 01-

0000018876-55

Classification

Aquatic Chronic 2 - H411

ZINC DISTEARATE 1-5%

CAS number: 557-05-1 EC number: 209-151-9 REACH registration number: 01-

2119982400-42

M factor (Acute) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Aguatic Acute 1 - H400

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards No specific precautions due to the small quantities handled.

Hazardous combustion

products

Oxides of carbon.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. For waste disposal,

see Section 13.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame.

Advice on general Do not eat, drink or smoke when using this product. No specific hygiene procedures

occupational hygiene recommended but good personal hygiene practices should always be observed when working

with chemical products.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from flammable and combustible materials. Store in closed original container at

temperatures between 5°C and 25°C.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

WEL = Workplace Exposure Limit

BENZOYL PEROXIDE (CAS: 94-36-0)

DNEL Industry - Dermal; Long term : 6.6 mg/kg/day

Industry - Oral; Long term : 1.6 mg/kg/day Industry - Inhalation; Long term : 11.75 mg/m³

PNEC - Sediment (Freshwater); 0.338 mg/kg

- marine water; 0.0000602 mg/l

- Sediment (Marinewater); 0.0338 mg/kg

- STP; 0.35 mg/l

- Fresh water; 0.000602 mg/l

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Wear protective gloves made of the following material: Nitrile rubber.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. DO NOT

SMOKE IN WORK AREA!

Respiratory protection No specific recommendations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Black.

Odour Characteristic.

Odour threshold Not determined.

pH Not determined.

Melting point Not applicable.

Initial boiling point and range Not applicable.

Flash point Not applicable.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas)

Not determined.

Upper/lower flammability or explosive limits

Not determined.

Other flammability Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 1.5 - 1.6

Bulk density

Solubility(ies)

Not determined.

Partition coefficient

Not determined.

Auto-ignition temperature

Not determined.

Decomposition Temperature >50°C

Viscosity > 60 S ISO2431

Explosive properties No information available.

Oxidising properties Not determined.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Acids. Alkalis. Amines. Strong reducing

agents.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Will decompose at

temperatures exceeding 50°C.

10.3. Possibility of hazardous reactions

Revision date: 05/12/2017

Super Hybrid SH-PRO comp B

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with strong reducing agents. Avoid heat. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong reducing agents. Acids, non-oxidising. Acids - organic. Alkalis - inorganic. Alkalis -

organic. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation Sensitising.

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Route of exposure Skin and/or eye contact.

Medical symptoms Skin irritation. Irritation of eyes and mucous membranes.

Medical considerations No information available.

Toxicological information on ingredients.

BENZOYL PEROXIDE

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

BENZOYL PEROXIDE

Acute aquatic toxicity

LE(C)₅₀ $0.01 < L(E)C50 \le 0.1$

M factor (Acute) 10

Acute toxicity - fish LC50, 96 hours: 0.06 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 0.11 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 0.07 mg/l, Selenastrum capricornutum

Chronic aquatic toxicity

M factor (Chronic) 10

BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 24 hours: > 1.23 mg/l, Cyprinus carpio (Common carp)

LC₅₀, 48 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) LC₅₀, 72 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) EC₅₀, 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) EC₁₀₀, 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) NOEC, 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp)

Acute toxicity - aquatic

invertebrates EC₅₀, 48 hours: > 2.2 mg/l, Daphnia magna

NOEC, 48 hours: > 2.2 mg/l, Daphnia magna

EC₅₀, 24 hours: > 2.2 mg/l, Daphnia magna

Acute toxicity - IC₅₀, 3 hours: > 1000 mg/l, Activated sludge microorganisms NOEC, 3 hours: > 1000 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility Mobile. The product is partly miscible with water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082
UN No. (ADN) 3082

14.2. UN proper shipping name

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

(ADR/RID) PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BENZOYL

PEROXIDE, BENZOIC ACID, NONYL ESTER, BRANCHED AND LINEAR)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID classification code M6

ADR/RID label 9

IMDG class 9

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group

ADN packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

ADR transport category 3

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 05/12/2017

 Version number
 2.000

 SDS number
 20998

Hazard statements in full H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.